

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number  
**WO 2004/044076 A1**

(51) International Patent Classification<sup>7</sup>: **C09G 1/02**,  
H01L 21/3105, 21/321

4-D, 3-3-3, Yadokawara, Tama-ku, Kawasaki-shi, Kanagawa-ken (JP). **BERAR, Pascal** [FR/US]; 2520 Barrington Court, Hayward, CA 94545 (US).

(21) International Application Number:  
PCT/US2003/036618

(74) Agents: **BALANCIA, Victor, N. et al.**; Pennie & Edmonds LLP, 1155 Avenue of the Americas, New York, NY 10036 (US).

(22) International Filing Date:  
13 November 2003 (13.11.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
JP2002-329464 13 November 2002 (13.11.2002) JP

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **EKC TECHNOLOGY, INC.** [US/US]; 2520 Barrington Court, Hayward, CA 94545 (US).

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicant (*for US only*): **EKC TECHNOLOGY K.K.** [JP/JP]; KSP R & D D342 3-2-1- Sakado, Takatsu-ku, Kawasaki, Kanagawa, 213-0012 (JP).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **NOJO, Haruki** [JP/JP]; 440 Kurami, Samukawamachi Kouza-Gun, Kanagawa-Ken (JP). **YOSHIDA, Akitoshi** [JP/JP]; 991-176, Yahagi-cho, Chuo-ku, Chiba-shi, Chiba-ken (JP). **KASHIHARA, Hirofumi** [JP/JP]; Mesonokura



**WO 2004/044076 A1**

(54) Title: A SLURRY COMPOSITION AND A POLISHING METHOD USING THE SAME

(57) Abstract: To provide a polishing slurry composition which effectively reduces the occurrence of scratches, and a method of polishing which reduces the occurrence of scratches while realizing an economical polishing step. The aforementioned object is attained by using a polishing slurry composition for polishing a semiconductor substrate containing a metal oxide particle, at least one water-soluble organic polymer and water, said slurry composition characterized in that, when a test substrate having a metal film, a shallow trench isolation film or dielectric film is polished by varying a rate of a polishing pad equipped in a polishing apparatus under a constant polishing pressure to achieve a maximum polishing rate.